

R 30 – push driven -



Photo doesn't show standard machine

PRACTICAL AND FUNCTIONAL

Technical details: R 30 - push driven - Weight: 180 kg. Dimension: 150x100x115 cm.





Revolving front wheel
(STANDARD)

Engine: petrol, 9.5 hp with recoil starter or electric start (optional) and clutch to facilitate starting.

Compressor: Fini capacity 556 lt/min.

Tank: 50 lt. (PED tested) with built-in mixer. Safety valves and check valves.

Spraying unit: composed of automatic gun for refracting and ordinary paints. Telescope unit with copy wheel, for lines from 10 cm to 30 cm.

Other standard equipment:

- Revolving front wheel
- Spraying device washing tank 6 lt
- Safety valves
- Check valves
- Mechanical brake on front wheel
- Regulators with accompanying glycerine pressure gauges to check pressures
- Telescopic indicator

Accessories available:

- Gun manual type (with rigid extension)
- Supplementary container for a different color (10 lt.)
- Automatic device for broken lines (pneumatic)
- Pneumatic spread glass beads device
- Electric start engine, revolving headlamp (LED) and deepness light (LED)
- Electronic device for broken lines (AEV1)





Spray guns, steel frame and mounting are strictly hand-made under strict controls and operational and robustness criteria. They guarantee high quality roadmarking machine and a high durability over time.